DBCLOUD
EXAMS

QUESTIONS & ANSWERS

verified



Technology Provider: Fortinet

Exam: Fortinet NSE 6 - FortiNAC-F 7.6 Administrator

Number of questions in the database: 26

Exam Version: NOV.2026

Question #1Topic1

When performing a wireless integration, what must be configured for FortiNAC-F to provide the MAC address information of a connecting device?

A. MAC notification traps

B. Link traps

C. RADIUS

D. Syslog messaging

Correct Answer: C

Question #2Topic1

A user had full corporate network and internet access for most of the day but has now been isolated and is redirected to a quarantine/remediation webpage. What would cause this behavior?

A. The logged on user is not found in the active directory.

B. The host has been marked as failed for an admin scan.

C. The host has been administratively disabled.

D. The host was removed from the Registered Hosts group.

Correct Answer: B

https://dbcloud.academy/

Question #3Topic1

Two FortiNAC-F devices have been configured in a 1+1 active-passive HA configuration. Which condition would cause the primary FortiNAC-F to shut down the NAC process and change the management status to down?

A. The primary misses five heartbeats and fails to ping the gateway.

B. The secondary takes control of the primary.

C. An administrator changes the status of the secondary to Running – In Control.

D. The primary fails to poll the secondary while the gateway responds successfully.

Correct Answer: A

Question #4Topic1

How are logical networks assigned to endpoints?

A. Through device profiling rules

B. Through FortiGate IPv4 policies

C. Through model configuration settings

D. Through network access policies

Correct Answer: D

Question #5Topic1

An administrator wants to incorporate a third-party security device to generate security events and alarms. The third-party device is configured to send syslog messages to FortiNAC-F.

Which two items must be completed? (Choose two.)

A. A security incident rule

B. A compliance policy

C. A security event parser

D. A trap MIB file

Correct Answer: AC

https://dbcloud.academy/

Question #6Topic1

During an initial installation, which configuration must be applied to allow for the modeling of infrastructure devices?

A. set allowaccess dns

B. set allowaccess snmp

C. set allowaccess radius-auth

D. set allowaccess dhcp

Correct Answer: B

Question #7Topic1

An administrator wants to use FortiNAC-F to collect an application inventory for hosts. Which two options would satisfy this requirement? (Choose two.)

A. Agent technology

B. MDM integration

C. Device profiling rules

D. Portal page on-boarding options

Correct Answer: AB

https://dbcloud.academy/

Question #8Topic1

Refer to the exhibit.

Device Profiling Rules - Total: 17

Rank: Set Rank Enable: Rogue Evaluation Queue Size:0 Detail Flush

Enabled	Rank	Name	Type	Registration	Methods	Register as Device
✔	1	Printer (DHCP)	Printer	Manual	DHCP	Host View
✔	2	APC - UPS	UPS	Automatic	Active, HTTP, Vendor OUI	Host View
✔	3	Medical Device	Health Care Device	Automatic	Vendor OUI	Host View
✔	4	FortiCamera (ONVIF)	Camera	Automatic	ONVIF	Host View
✔	5	Printer (TCP:80,515,9100)	Printer	Manual	TCP	Host View
⊘	6	Android (DHCP)	Android	Automatic	DHCP	Host View

If a device connects to the network for the first time, and FortiNAC-F does not receive a DHCP fingerprint, what would be the next step in the device profiling process?

A. The device would be modeled as a generic device.

B. After 5 minutes, the device would be evaluated against the next rule.

C. The FortiNAC-F would attempt to get a session fingerprint from a modeled firewall.

D. The device would be added to the database as a rogue.

Correct Answer: D

Question #9Topic1

A network administrator wants to use network access policies to define access for different types of hosts. Which group must be populated with all the possible points of connection?

A. Forced Registration

B. Role-Based access

C. Authorized access points

D. Forced Remediation

Correct Answer: B

https://dbcloud.academy/